




Manual, radial-arm, crosscut saw

JUNIOR 640

For straight (90°) miter (45° left) cross cutting, and bevel cutting at 45° left and right, of wooden-based panels and solid wood boards up to 3mt. For furniture manufacturing and joinery.









VERSATILE

Swivelling arm (0° to 45° left and right) and tilting cutting-head (stop and lock at 45° left) allow many different cutting operations for the greatest versatility.

SAFE

Sound-insulated, full-cover blade guard with safety microswitch, anti-kickback, well-dimensioned working bench, emergency button definitively contribute to the operator safety during the cutting process.

SOLID AND ACCURATE

Rugged steel construction, arm and base made of cast iron.

Interchangeable and tempered-steel made guides. Cutting head sliding on 8 ball bearings for a smooth, precise and effortless carriage mouvement.

Small footprint: well suited to small workshops

Easy to use

Versatile

Useful complement to panel saws



JUNIOR 640 SERVICE

Worldwide after-sale service.

Real-time, on-line remote assistance through a dedicated augmented reality APP. Spare-parts availability for up to 10 years, shipment within 24 hrs

DATA SHEET

Many analytican lead what	105
Max. cutting height:	125 mm
Max. cutting width	545 x 20 h mm
Mincutting width	450 x 125 h mm
Max.length of workpiece	unlimited
Cutting height at 45°	0 - 80 mm
Min. and Max. cutting width at 45° (right)	315 - 380 mm
Min. and Max. cutting width at 45° (left)	125 - 190 mm
Height of blade from working bench	0 - 45 mm
Blade diameter	400 mm
Blade bore diameter	30 mm
Motor	HP / KW 4/3 RPM 2800
Working bench dimensions	15470x1025mm
Diameter of dust collection nozzle on blade guard	60 mm
Diameter of dust collection nozzle on rear hood	100 mm
Overall dimensions of full- assembled machine	1540x1375x1540 mm
Package dimensions and weight	1420x850x600 mm 232 Kg



THE MOST POPULAR

Cutting width up to 545 mm. Allaround performance. Well-suited also for the hobbyist.

CUTTING HEIGHT

CUTTING



WIDTH

↑ MAX JUNIOR 640 **BIG 800 BEST 960 BEST 1250** 90° **45**° ∟ **45°** R **45°** ∟ **45°** ℝ 90° **45°** ℝ mm mm mm mm mm mm mm mm 450 610 770 1060 776 1066 616 464 624 784 1074 634 794 1084 95 Ø 400 mm mm 80 486 646 806 1096 65 661 821 1111 680 840 1130 35 705 865 425 1155 800 20

MIN mm MAX

SERVICE +39 0571 635 433

service@maggi-technology.com

SALES

+39 0571 635 474 sales@maggi-technology.com



MAGGI TECHNOLOGY

Via delle Regioni, 299 50052 Certaldo (Firenze) Italia